Qualitel

1200Mbps
802.11ac/b/g/n Dual-Band Concurrent 4-Port Gigabit WLAN AP Router (RE1200R4GC-2T2R-V3)

Dual-Band 1.2Gbps | **ac 802.11** | **n 802.11** | **b/g 802.11** | **1200 Mbps** | **Dual-Band** | **Easy Setup** | **Firewall** | **QoS Streaming** | **4-Port** | **WPS** | **WLAN ON/OFF** | **Parental Control**

WiFi specification

- Operating Frequency : 2.412G~2.484GHz
- Operating Frequency : 5.1G~5.8GHz
- Supports 802.11b data rates of up to 11 Mbps with automatic fallback to 5.5, 2, and1 Mbps
- Supports 802.11g data rates of up to 54 Mbps with automatic fallback to 48, 36, 24,18, 12, 9, and 6 Mbps
- Support 802.11n (MIMO 2T2R): Up to 300Mbps (MCS15)
- 802.11ac 2T2R: 866Mbps (5Ghz)
- Security supports 64/128-bits WEP, WPA,WPA2, WPS
- Multi-SSID

Ethernet WAN specification

- WAN:10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- WAN IP Assignment
  - Static IP
  - DHCP client
  - PPPoE client

LAN specification

- LAN:10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port

Features

- IGMP snooping and IGMP proxy
- VPN pass through
- Management - HTTP Web-based Configuration

Hardware interface

- DC Power jack
- Power switch to power on /off device
- Reset button to factory defaults
- 1 x WAN:10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- 4 x LAN:10 / 100 / 1000Mbps Auto-MDI / MDI-X RJ-45 Ethernet port
- 2 x 5dbi Dual Band Antenna
- WiFi ON/OFF, WPS switch button

Operating Environment

- Operating temperature: 0 − 40°C
- Storage temperature: -20 − 70°C
- Humidity: 20 − 95% non-condensing